



Frostvakt 25

Self-regulating 2-conductor with screen

Usage

- For metal and plastic gutters and downpipes
- Externally on Ø 75 mm pipes or larger

Self-regulating 25 W/m Plug

- ✓ Energy efficient
- ✓ Can be crossed during installation

Frostvakt 25 has a 4 metre long, pre-assembled connection cable with plug and is ideal for use for temporary installations in gutters and downpipes. You can easily secure it to the gutter using Ebeco Smartclip and connect to a 230 V earthed socket, via a residual current device (RCD). Frostvakt 25 can be used on the outside of Ø 75 mm or larger pipes. A Ø 110 mm pipe with 20 mm insulation can withstand temperatures down to -30°C when protected with Frostvakt 25.

Specifications

Connection voltage	230 V
Connectors	Plug
Number of conductors	2 pcs
Bending radius, min.	35 mm
Output	Approx. 25 W/m at + 10° C (air), Approx. 45 W/m (snow and ice)
Exposure temperature (power off), max.	85 °C
Installation temperature, min.	-40 °C
Insulation material inner	EVA, LDPE
Insulation material outer	EVA, LDPE
Cable type	Self-regulating 2-conductor with screen
Enclosure class	Plug: IP44, cable: IP67
Conductor area	1,16 mm²
Exposure temperature (power on), max.	Up to 65 °C
Dimensions	10,5 * 6,0 mm
Protective conductor	Braided
UV resistance	Yes

Documents

 CE document

 Manual

Warranty

Below is a list of our general delivery terms.
[Our warranty terms](#)

Article list

Article number	Length (m)	Output (W)
8960471	5	125
8960472	8	200
8960473	12	300
8960474	16	400
8960475	20	500
8960476	25	625
8960477	30	750

Feel free to complete



Frostvakt
Control



Smartclip

Learn more about this product:<https://www.ebeco.com/products/frost-protection-pipes/frostvakt-25>