

Foil 230 V

Parallel-resistive heating foil

Usage

- Underfloor heating for wooden floors, laminate floors and linoleum
- Underfloor heating only for dry areas
- Placed on concrete, plaster or chipboard

 Foil  65 W/m²  Running metres

- ✓ Extremely low installation height
- ✓ Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	230 V
Max connection area at 10 A, max.	35 m²
Output	65 W/m²
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents



CE
document



Manual

Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised


electrician and documented in Ebeco's Garantera service.

[Our warranty terms](#)


Article list

Article number	Width (m)	Output (W/m)	Output (W/m ²)
8960606	-	43	100
8960608	-	69	-
8960626	0.43	26	65
8960628	0.69	43	65
8960627	1	65	65

The product is included in:




[Foil Kit 500](#)



[Foil Kit 500](#)

Feel free to complete



[EB-Therm
500](#)



[RTK cable](#)



[Connection
clamp](#)

Learn more about this product:

<https://www.ebeco.com/products/underfloor-heating/foil-230-v>