



Snowmelt

Series-resistive 2-conductor with screen on elastic mesh

Usage

- Snow melting installations
- Laid in a sand bed or embedded in concrete

 Elastic mesh  200-300 W/m²

- ✓ Quick and easy placement
- ✓ Robust and durable
- ✓ Elastic and adaptable

Snowmelt is an elastic heating cable mat consisting of a heating cable secured to rubber bands. By stretching the mat out, the c/c distance is increased and thus the effect is reduced. This unique design reduces the installation time by about 75% compared to conventional mounting on straps. The heating cable has a built-in dual conductor cable, which means there is only one end to connect. The heating cable mat is placed in a sand bed under asphalt or paving. It can also be embedded in concrete. The mat should be laid at least 30 mm deep.

Specifications

Connection voltage	230 V
Length Connection cable	5,0 m
Number of conductors	2 pcs
Output range	200 - 300 W/m ²
Installation temperature, min.	-5 °C
Insulation material intermediate	XLPE
Insulation material inner	ETFE
Insulation material outer	PVC
Cable type	Series-resistive 1-conductor with screen
Enclosure class	IP67
Mat	Rubber band
Protective conductor	Braided
UV resistance	Yes

Documents



CE
document



Manual

Warranty



10 year product guarantee in case of material defects.

[Our warranty terms](#)


Article list

Article number	Width (m)	Length interval (m)	Output (W)	Length interval (m2)
8960290	0.5	14.0 - 22.0	2200	7.0 - 11.0
8960292	1	9.0 - 13.5	2700	9.0 - 13.5
8960294	1	12.0 - 18.0	3600	12.0 - 18.0
8960296	1	14.0 - 21.5	4250	14.0 - 21.5

Feel free to complete



[Quick Board](#)



[EB-Therm
500](#)



[Timer](#)



[Ground sensor](#)



[Electrical
enclosure](#)



[Mini electrical
enclosure](#)

Learn more about this product:<https://www.ebeco.com/products/snow-melting-ground/snowmelt>