



F-10

Self-regulating 2-conductor with screen

Usage

- For water and sewage pipes, drains and wells
- For internal and external installation
- Drinking water approved

 Self-regulating  10-20 W/m  Running metres

- ☑ Energy efficient
- ☑ Meets the requirements for drinking water
- ☑ Can be cut and crossed for perfect adaptation

F-10 is a self-adjusting heating cable that detects the ambient temperature and adjusts output accordingly. Used for external and internal frost protection of pipes. The cable can be cut and crossed for perfect adaptation to the pipe. Meets the requirements for drinking water according to KTW and NSF/ANSI Standard 61.



Produkten bedömd i
SundaHus

Specifications

Connection voltage	230 V
Number of conductors	2 pcs
Bending radius, min.	25 mm
Output	10 W/m at 10°C
Exposure temperature (power off), max.	65 °C
Installation temperature, min.	-45 °C
Insulation material inner	PP
Insulation material outer	ECTFE
Cable type	Self-regulating 2-conductor with screen
Enclosure class	IP68
Conductor area	0,56 mm ²
Exposure temperature (power on), max.	Up to 65 °C
Protective conductor	Aluminium foil
UV resistance	Yes

Documents



CE
document



Manual



Type approval certificate

Warranty



10 year product guarantee in case of material defects.

[Our warranty terms](#)


Article list

Article number	Dimensions (mm)	Output (W/m at 10° C)
8960460	7,0 * 5,0	10

Feel free to complete



[EB-Therm
800](#)



[Y-coupling](#)



[Supplementary
kit F-10](#)



[F-10 silicone
connection/end
kit](#)

Learn more about this product: <https://www.ebeco.com/products/frost-protection-pipes/f-10>