



T-18

Self-regulating 2-conductor with screen


Usage

- Part of our Smarta Tak solution
- For metal and plastic gutters and downpipes

 Self-regulating  18-36 W/m  Running metres

- ✓ Energy efficient
- ✓ Can be cut and crossed for perfect adaptation
- ✓ Smart accessories

Self-regulating heating cable that detects the ambient temperature and adjusts output accordingly. Part of our Smarta Tak solution. With its thermoplastic outer casing, it is well suited for laying in gutters and downpipes made of metal and plastic. Complemented by other products and accessories within our Smarta Tak solution.



Specifications

Connection voltage	230 V
Number of conductors	2 pcs
Bending radius, min.	25 mm
Output	15 W/m at 10°C
Exposure temperature (power off), max.	80 °C
Installation temperature, min.	-50 °C
Insulation material inner	PP
Insulation material outer	PP
Cable type	Self-regulating 2-conductor with screen
Conductor area	1,23 mm ²
Exposure temperature (power on), max.	Up to 65 °C
Protective conductor	Aluminium foil
UV resistance	Yes

Documents



CE
document



Manual

Warranty



10 year product guarantee in case of material defects.

[Our warranty terms](#)

Article list

Article number
8960480

Dimensions (mm)
11,8 * 5,7

Feel free to complete



[Smartlock](#)



[Smartclip](#)



[EB-Therm
800](#)



[Roof sensor](#)



[Electrical
enclosure](#)



[Mini electrical
enclosure](#)

Learn more about this product:<https://www.ebeco.com/products/snow-melting-roof/t-18>